

Rhinolon™ P93U



FEATURES

- High wear resistance
- High extrusion resistance
- Good oil resistance
- Good rebound resistance
- Good tear resistance
- Good compression set resistance

PRODUCT DESCRIPTION

Code: P93U
 Color: Black
 Description: 93D Shore A Polyurethane

Property	Value	Unit	Value	Unit
Tensile Strength, Yield	6,815	PSI	47	MPa
Tensile Elongation, Break	480	%	480	%
Service Temperature Range	-40 to 230	°F	-40 to 110	°C
Specific Gravity	1.19	-	1.19	-
Hardness	93	Shore A	93	Shore A
Moisture Absorption	0	%	0	%
Compression Set, 24 hrs @ 70°C	23	%	23	%
Modulus @ 100%	1,885	PSI	13	MPa

April 1, 2017

This information corresponds to our current information on this material. It is provided solely to provide guidelines for your evaluation. This information is not intended to substitute for any testing you may need to conduct to determine the suitability of our products for your particular application. Since we cannot anticipate all variations of the actual end use application conditions, we do not make any warranties or assume any liabilities in connection with any use of this information.

Product Performance. Affordability. Availability.



10515 Majic Port Lane | Fort Wayne, IN 46819 | USA
 Telephone: 260-615-3951 | Fax: 260-436-5267
 info@BlackHawkSeals.com