## Rhinolon™ P98U



### FEATURES

- High wear resistance
- High extrusion resistance
- High tear resistance
- Low moisture absorption
- Excellent fluid resistance

#### **PRODUCT DESCRIPTION**

# Code:P98UColor:Sky BlueDescription:98DShore APolyurethane

| Property                  | Value       | Unit    | Value      | Unit    |
|---------------------------|-------------|---------|------------|---------|
| Tensile Strength, Yield   | 6,525       | PSI     | 45         | MPa     |
| Tensile Elongation, Break | 460         | %       | 460        | %       |
| Service Temperature Range | -40 to 250° | °F      | -40 to 120 | °C      |
| Specific Gravity          | 1.19        | -       | 1.19       | -       |
| Hardness                  | 98          | Shore A | 98         | Shore A |
| Moisture Absorption       | 0           | %       | 0          | %       |
| Modulus @ 100%            | 1,960       | PSI     | 13.5       | MPa     |

#### April 1, 2017

This information corresponds to our current information on this material. It is provided solely to provide guidelines for your evaluation. This information is not intended to substitute for any testing you may need to conduct to determine the suitability of our products for your particular application. Since we cannot anticipate all variations of the actual end use application conditions, we do not make any warranties or assume any liabilities in connection with any use of this information.

Product Performance. Affordability. Availability.



10515 Majic Port Lane | Fort Wayne, IN 46819 | USA Telephone: 260-615-3951 | Fax: 260-436-5267 info@BlackHawkSeals.com