

Product Performance. Affordability. Availability.



3702 Vanguard Drive | Fort Wayne, IN 46809 | USA 260-615-3951 | info@BlackHawkSeals.com BlackHawkSeals.com **AN1** ROD WIPER

The **AN1 Rod Wiper** improves the wiping performance in light to medium duty hydraulic and pneumatic cylinders by removing contamination, dust, and debris from the cylinder rod. Exclusion technology ribs on the outer diameter of the wiper enhance exclusion performance by preventing contaminants and moisture from forming on the outer diameter of the wiper. The slotted heel prevents fluid from pressure trapping between the seal and wiper and maintains stability of the wiper in the groove. The **AN1** is molded from a high-performance polyurethane material for cost efficiency and performance criteria.

The **AN1 Rod Wiper** is designed to fit standard MS-28776 (MS-33675) AN Wiper dash size grooves. Recommended for light to medium duty hydraulic and pneumatic cylinder applications where space constraints on the rod gland are necessary.

STANDARD MATERIALS

Material Code	Material Description	Color	all & hade
P95U	Polyurethane 95D Shore A	Black	
Other material options	are available upon request.		
FEATURE	=5		
Excellent Exclusion Performance			
 Low Temperature (-40°F) 			
 High Temperature (+225°F) 			
Velocity up to 3 FPS			
Low Compression Set			
Low Friction	N N		
Cost Effective			
Compact Size			
• Easy Installation			
 Fits Standard MS 	S-28776 (MS-33675) AN Wiper Size Groove	es	

