



FEATURES

- High wear resistance
- High extrusion resistance
- Low friction
- Low moisture absorption
- Excellent fluid resistance
- Cost effective

PRODUCT DESCRIPTION

Code: T20
 Color: Greyish Black
 Description: Glass fiber reinforced PTFE plus self-lubricating additive

Property	Value	Unit	Value	Unit
Tensile Strength, Yield (ASTM D1457)	2,800	PSI	19	MPa
Tensile Elongation, Break (ASTM D1457)	200	%	200	%
Service Temperature Range	-65 to 400	°F	-54 to 205	°C
Specific Gravity	2.25	-	2.25	-
Hardness	60	Shore D	60	Shore D
Moisture Absorption	0	%	0	%

March 15, 2018

This information corresponds to our current information on this material. It is provided solely to provide guidelines for your evaluation. This information is not intended to substitute for any testing you may need to conduct to determine the suitability of our products for your particular application. Since we cannot anticipate all variations of the actual end use application conditions, we do not make any warranties or assume any liabilities in connection with any use of this information.

Product Performance. Affordability. Availability.



10515 Majic Port Lane | Fort Wayne, IN 46819 | USA
 Telephone: 260-615-3951 | Fax: 260-436-5267
 info@BlackHawkSeals.com | BlackHawkSeals.com